


Cam follower CFES12-1-BUU-IKO - CFES12-1-BUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfes12-1-buu-iko>



CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers With Cage/With Hexagon Hole



CFES-BUU

Stud dia. mm	Identification number										Mass (Ref.)		D	C	d ₁	
	Shield type					Sealed type					g	C				
	With crowned outer ring		With cylindrical outer ring			With crowned outer ring		With cylindrical outer ring								
12						CFES 12-1 BUU					105	32	14	12		
Boundary dimensions mm																
G	G ₁	B _{max}	B ₁ _{max}	B ₂	B ₃	C ₁	s ₁	s ₂	H	ε _{max}	ε	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M12×1.5	13	15.2	40.2	25	6	0.6	6	3	6	0.6	0.4	21	21.9	7 910	9 790	9 790

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952443607
Inside diameter	12 mm
Outside diameter	32 mm
Thickness	14 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE