

Cam follower CFES18-BUUR-IKO - CFES18-BUUR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfes18-buur-iko>



CAM FOLLOWERS

Solid Eccentric Stud Type Cam Followers With Cage/With Hexagon Hole



CFES-BUUR

Stud dia. mm	Identification number										Mass (Ref.)					
	Shield type					Sealed type					g	D	C	d _i		
	With crowned outer ring		With cylindrical outer ring			With crowned outer ring		With cylindrical outer ring								
18			CFES 18			BUUR			250	40	20	18				
Boundary dimensions mm																
G	G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	H	H _{max}	Excentricity ε	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M18×1.5	19	21.6	58.1	36.5	8	0.8	6	3	8	1	0.6	29	86.2	14 800	25 200	25 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952443676
Inside diameter	18 mm
Outside diameter	40 mm
Thickness	20 mm
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE