


Cam follower CFE6-IKO - CFE6-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe6-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		ϕ	D	C	d_2
9	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	20.5	16	11	9
	CFE 6							

Boundary dimensions mm														
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	$\frac{f}{\text{mm}}$	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N			
M 6×1	7.5	12.2	28.2	16	0.6	*4	8.5	0.3	0.4	11	2.7	3 660	3 650	1 950

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459763
Inside diameter	9 mm
Outside diameter	16 mm
Thickness	11 mm
Weight	20 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE