


## Cam follower CFE12-1-UUR-IKO - CFE12-1-UUR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe12-1-uur-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		$\emptyset$	D	C	$d_2$
16	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	115	32	14	16
<b>CFE 12-1 UUR</b>								

Boundary dimensions mm														
G	B <sub>3</sub>	B <sub>1</sub> max	B <sub>2</sub> max	C <sub>1</sub>	G <sub>1</sub>	( <sup>1</sup> ) r <sub>max</sub>	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable axial load N			
M 8×1.25	9.5	12.2	32.2	20	0.6	*4	10.5	0.3	0.4	13	6.5	4 250	4 740	4 620

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459947
Inside diameter	16 mm
Outside diameter	32 mm
Thickness	14 mm
Weight	115 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE