


Cam follower CFE18-UUR-IKO - CFE18-UUR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe18-uur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		\emptyset	D	C	d_2						
24	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	280	40	20	24						
CFE 18 UUR														
Boundary dimensions mm														
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	α	Mounting dimension f mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N			
M18×1.5	17.5	21.6	58.1	36.5	0.8	6	19	1	0.8	29	86.2	14 800	25 200	25 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460011
Inside diameter	24 mm
Outside diameter	40 mm
Thickness	20 mm
Weight	280 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE