

Cam follower CFE20-1-IKO - CFE20-1-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe20-1-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

Outside diameter of eccentric roller mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d ₂
	With crowned outer ring	With cylindrical outer ring	CFE 20-1	With crowned outer ring	With cylindrical outer ring					
27			CFE 20-1				425	47	24	27

Boundary dimensions mm											Eccentricity g	Mounting dimension f mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B max	B ₁ max	B ₂	C ₁	G ₁	(1) r _{max}									
M20 X 1.5	19.5	25.6	66.1	40.5	0.8	8	21	1	0.8	34	119	20 700	34 600	34 600		

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460080
Inside diameter	27 mm
Inside diameter	1.063" inch
Outside diameter	47 mm
Outside diameter	1.85" inch
Thickness	24 mm
Thickness	0.945" inch
Weight	425 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE