

Cam follower CFE6-VB-IKO - CFE6-VB-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe6-vb-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



Outside diameter of axle mm	Identification number						Mass (Ref.)			
	Shield type		Sealed type				g	D	C	d _e
9	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring			21	16	11	9

Boundary dimensions mm											Eccentricity	Mounting dimension	Maximum tightening torque	Basic dynamic load rating	Basic static load rating	Maximum allowable static load
G	B_3	$B_{\max}$	$B_{1\max}$	B_2	C_1	g_1	G_1	H	$f_{\max}$ (°)	f Min. mm	ϵ	N·m	C	C_0	N	
M 6×1	7.5	12.2	28.2	16	0.6	—	8.5	3	0.3	0.4	11	2.7	6 980	8 500	1 950	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460301
Inside diameter	9 mm
Outside diameter	16 mm
Thickness	11 mm
Weight	21 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE