


Cam follower CFE8-VBUU-IKO - CFE8-VBUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe8-vbuu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUU

Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)								
	Shield type		Sealed type		Ø	D	C	d _e							
11	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 8	VBUU	32.5	19	11	11					
Boundary dimensions mm															
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	H	f _{max} (°)	f Min. mm	Mounting torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N			
M 8 X 1.25	9.5	12.2	32.2	20	0.6	—	10.5	4	0.3	0.4	13	6.5	8 170	11 200	4 620

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460332
Inside diameter	11 mm
Inside diameter	0.433" inch
Outside diameter	19 mm
Outside diameter	0.748" inch
Thickness	11 mm
Thickness	0.433" inch
Weight	32.5 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE