

Cam follower CFE8-VB-IKO - CFE8-VB-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe8-vb-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
11	CFE 8 VB						32.5	19	11	11

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	H	Excentricity g	Flange E	Flange F						
M 8 × 1.25	9.5	12.2	32.2	20	0.6	—	10.5	4	0.3	0.4	13	6.5	8 170	11 200	4 620

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460356
Inside diameter	11 mm
Outside diameter	19 mm
Thickness	11 mm
Weight	32.5 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE