

Cam follower CFE10-VBUUR-IKO - CFE10-VBUUR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe10-vbuur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole

Outside diameter of eccentric collar mm	Identification number				Mass (Ref.)										
	Shield type		Sealed type		ϕ	D	C	d_e							
13	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	50.5	22	12	13							
CFE 10 VBUUR															
Boundary dimensions mm															
G	B_3	B_{max}	B_1	B_2	C_1	G_1	H	f	Mounting dimension	Maximum splining torque	Basic dynamic load rating	Basic static load rating	Maximum allowable static load		
M10 × 1.25	10.5	13.2	36.2	23	0.6	—	12.5	4	0.3	0.4	16	13.8	9 570	14 500	8 650

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460400
Inside diameter	13 mm
Inside diameter	0.512" inch
Outside diameter	22 mm
Outside diameter	0.866" inch
Thickness	12 mm
Thickness	0.472" inch
Weight	50.5 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE