


Cam follower CFE12-VBUU-IKO - CFE12-VBUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe12-vbuu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUU

| Outside diameter of eccentric roller mm | Identification number | | | | | | Mass (Ref.) | | | | | | | |
|---|-------------------------|-----------------------------|-------------------------|-----------------------------|----------------|------|-------------|--------------------|-------------------------|---------------------------|--------------------------|-------------------------------|--------|--------|
| | Shield type | | | Sealed type | | | ø | D | C | d _e | | | | |
| 16 | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | CFE 12 | VBUU | | | | | 107 | 30 | 14 | 16 |
| Boundary dimensions mm | | | | | | | | | | | | | | |
| G | B ₃ | B ₁ max | B ₂ max | C ₁ | G ₁ | H | f | Mounting dimension | Maximum splining torque | Basic dynamic load rating | Basic static load rating | Maximum allowable static load | | |
| M12×1.5 | 11.5 | 15.2 | 40.2 | 25 | 0.6 | 6 | 13.5 | 6 | 0.6/0.8 | 21 | 21.9 | 13 500 | 19 700 | 13 200 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060460486 |
| Inside diameter | 16 mm |
| Inside diameter | 0.63" inch |
| Outside diameter | 30 mm |
| Outside diameter | 1.181" inch |
| Thickness | 14 mm |
| Thickness | 0.551" inch |
| Weight | 107 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE