

Cam follower CFE16-VBUU-IKO - CFE16-VBUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe16-vbuu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUU

Outside diameter of outer ring mm	Identification number								Mass (Ref.)			
	Shield type				Sealed type				Ø	D	C	d _e
	With crowned outer ring		With cylindrical outer ring		With crowned outer ring		With cylindrical outer ring					
22					CFE 16 VBUU				193	35	18	22

Boundary dimensions mm														
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	G ₁	H	H _{max} (*)	Eccentricity g	f Min. mm	Mounting dimension Maximun splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M16 X 1.5	15.5	19.6	52.1	32.5	0.8	6	17	6	0.6/0.8	26	58.5	20 700	37 600	23 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460561
Inside diameter	22 mm
Outside diameter	35 mm
Thickness	18 mm
Weight	193 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE