

Cam follower CFE20-VBUU-IKO - CFE20-VBUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe20-vbuu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUU

Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)								
	Shield type			Sealed type			Ø	D	C	d _e					
27	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 20	VBUU					505	52	24	27	
Boundary dimensions mm															
G	B ₃	B ₁ _{max}	B ₂ _{max}	B ₂	C ₁	G ₁	H	f _{max}	f	Mounting dimension	Maximum splining torque	Basic dynamic load rating	Basic static load rating	Maximum allowable static load	
M20 X 1.5	19.5	25.6	66.1	40.5	0.8	8	21	8	1	0.8	34	119	33 200	64 500	37 500

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460639
Inside diameter	27 mm
Outside diameter	52 mm
Thickness	24 mm
Weight	505 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE