

Cam follower CFE10-1-V-IKO - CFE10-1-V-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe10-1-v-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _a
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
13		CFE 10-1 V			66	26	12	13

Boundary dimensions mm									
G	B ₃	B ₂ max	B ₁ max	B ₂	C ₁	g ₁	G ₁	r ₁ max	E
M10 X 1.25	10.5	13.2	36.2	23	0.6	*4	12.5	0.3	0.4

Mounting dimension f Min.	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
16	13.8	9 570	14 500	8 650

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460981
Inside diameter	13 mm
Outside diameter	26 mm
Thickness	12 mm
Weight	66 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE