


Cam follower CFE10-1-VUU-IKO - CFE10-1-VUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe10-1-vuu-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**



CFE10-1-VUU

Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
13				CFE 10-1 VUU	66	26	12	13

Boundary dimensions mm														
G	B ₃	B _{max}	B ₂ _{max}	B ₂	C ₁	g ₁	G ₁	r ₁ ⁽¹⁾ _{min}	Eccentricity E	Mounting dimension f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M10 × 1.25	10.5	13.2	36.2	23	0.6	*4	12.5	0.3	0.4	16	13.8	9 570	14 500	8 650

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461001
Inside diameter	13 mm
Outside diameter	26 mm
Thickness	12 mm
Weight	66 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE