

## Cam follower CFE20-1-VR-IKO - CFE20-1-VR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe20-1-vr-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d <sub>0</sub>
27	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	430	47	24	27

  

Boundary dimensions mm														
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>2max</sub>	B <sub>2</sub>	C <sub>1</sub>	B <sub>1</sub>	G <sub>1</sub>	r <sub>1min</sub> (°)	Eccentricity E	Mounting dimension f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
M20 × 1.5	19.5	25.6	66.1	40.5	0.8	8	21	1	0.8	34	119	33 200	64 500	37 500

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461209
Inside diameter	27 mm
Outside diameter	47 mm
Thickness	24 mm
Weight	430 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE