

Cam follower CFE30-1-VR-IKO - CFE30-1-VR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cfe30-1-vr-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.) g	D	C	da
	Shield type		Sealed type					
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
41	CFE 30-1 VR				2 190	85	35	41

Boundary dimensions mm										Eccentricity E	Mounting dimension f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C0 N	Maximum allowable static load N
G	B3	Bmax	B1max	B2	C1	g1	G1	r1min							
M30 × 1.5	32.5	37	100	63	1	8	30.5	1	1.5	49	438	67 700	144 000	85 900	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461346
Inside diameter	41 mm
Outside diameter	85 mm
Thickness	35 mm
Weight	2190 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE