


Cam follower CF6-WBR-IKO - CF6-WBR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf6-wbr-iko>

IKO

CAM FOLLOWERS

Thrust Disk Type Cam Followers With Cage/With Hexagon Hole



Stud dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Shield type	Sealed type		D	C	d ₁	G	G ₁
6	CF 6	WBR	18.5	16	11	6	M 6 x 1	8

B	B ₁	B ₂	B ₃	C ₁	E ₁	E ₂	H	Mounting dimension f Min. mm	Maximum tightening torque N.m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
12.2 max	28.2 max	16	—	0.6	—	—	3	11	2.7	3 660	3 650	1 950

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952458465
Inside diameter	6 mm
Outside diameter	16 mm
Thickness	11 mm
Weight	18.5 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE