


Cam follower CF-FU1-6-IKO - CF-FU1-6-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf-fu1-6-iko>

IKO

CAM FOLLOWERS

Centralized Lubrication Type Cam Followers With Cage/With Screwdriver Slot



| Stud dia. mm | Identification number | | Mass (Ref.) g | Boundary dimensions mm | | | | |
|-----------------|----------------------------|--------------------------------|---------------------|------------------------|----|----------------|---------|----------------|
| | With crowned outer ring | With cylindrical outer ring | | D | C | d ₁ | G | G ₁ |
| 6 | | CF-FU1-6 | 18.5 | 16 | 11 | 6 | M 6 x 1 | 8 |

| B _{max} | B _{1max} | B ₂ | B ₃ | C ₁ | g ₂ | M ₁ | M ₂ | f _s min ⁽¹⁾ | Mounting dimension f Min. mm | Maximum tightening torque N-m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
|------------------|-------------------|----------------|----------------|----------------|----------------|----------------|----------------|-----------------------------------|--|--|--|--|--|
| 12.2 | 28.2 | 16 | — | 0.6 | — | MBx | 0.75 | 0.3 | 11 | 2.7 | 3 660 | 3 650 | 1 950 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060461537 |
| Inside diameter | 6 mm |
| Outside diameter | 16 mm |
| Thickness | 11 mm |
| Weight | 18.5 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE