


Cam follower CF-FU1-24-1-IKO - CF-FU1-24-1-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf-fu1-24-1-iko>

IKO

CAM FOLLOWERS

Centralized Lubrication Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	With crowned outer ring	With cylindrical outer ring		D	C	d ₁	G	G ₁
24		CF-FU1-24-1	1 140	72	29	24	M24 x 1.5	25

B _{max}	B _{1max}	B ₂	B ₃	C ₁	g ₂	M ₁	M ₂	f ₆ min ⁽¹⁾	Mounting dimension f ₁ Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C	Basic static load rating C ₀	Maximum allowable static load
30.6	80.1	49.5	11	0.8	4	PT 1/8	PT 1/8	1	40	215	30 500	52 600	52 000

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461728
Inside diameter	24 mm
Outside diameter	72 mm
Thickness	29 mm
Weight	1140 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE