


Cam follower CF-FU1-30-2-IKO - CF-FU1-30-2-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cf-fu1-30-2-iko>

IKO

CAM FOLLOWERS

Centralized Lubrication Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number						Mass (Ref.) g	Boundary dimensions mm				
	With crowned outer ring			With cylindrical outer ring				D	C	d ₁	G	G ₁
30				CF-FU1-30-2			2 220	90	35	30	M30 x 1.5	32

B _{max}	B _{1max}	B ₂	B ₃	C ₁	g ₂	M ₁	M ₂	f ₆ min ⁽¹⁾	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
37	100	63	15	1	4	PT 1/8	PT 1/8	1	49	438	45 400	85 100	85 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461797
Inside diameter	30 mm
Outside diameter	90 mm
Thickness	35 mm
Weight	2220 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE