

Cam follower CR14-B-IKO - CR14-B-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr14-b-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
9.525 ($\frac{3}{8}$)	CR 14 B				46	22.225 $\frac{7}{16}$	12.700 $\frac{1}{2}$	9.525 $\frac{7}{16}$	$\frac{7}{16}$ -24	9.525 $\frac{7}{16}$	
Boundary dimensions mm/inch											
B max	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm (mm/inch)	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
14.2 0.56	22.225 $\frac{7}{16}$	6.350 $\frac{1}{4}$	0.794 $\frac{1}{16}$	4.762 $\frac{3}{16}$	2.381 $\frac{3}{32}$	4.762 $\frac{3}{16}$	0.794 $\frac{1}{16}$	15.081 $\frac{5}{16}$	10.6	4 790	5 910

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462459
Inside diameter	9.525 mm
Outside diameter	22.225 mm
Thickness	12.7 mm
Weight	46 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE