


Cam follower CR16-BUUR-IKO - CR16-BUUR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr16-buur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
11.112 ($\frac{7}{16}$)	CR 16 BUUR				73	25.400 (1)	15.875 ($\frac{5}{8}$)	11.112 ($\frac{7}{16}$)	$\frac{1}{2}$ -20	12.700 ($\frac{1}{2}$)	
Boundary dimensions mm/inch											
B max	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm(inch)	Maximum spinning torque C N·m	Basic static load rating C N	Basic static load rating C ₀ N
17.3 (0.68)	25.400 (1)	8.350 ($\frac{1}{3}$)	0.794 ($\frac{1}{16}$)	4.782 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	6.350 ($\frac{1}{4}$)	1.191 ($\frac{1}{16}$)	17.859 ($\frac{5}{8}$)	17.4	8 910	10 800

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462497
Inside diameter	11.112 mm
Outside diameter	25.4 mm
Thickness	15.875 mm
Weight	73 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE