

Cam follower CR20-BR-IKO - CR20-BR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr20-br-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole

Stud dia. mm (inch)	Identification number				Mass (Ref.)	g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring							
12.700 (1/2)	CR 20	BR			132	31.750 (1 1/4)	19.050 (3/4)	12.700 (1/2)	1.200 (1/2)	15.875 (5/8)	15.875 (5/8)
Boundary dimensions mm(inch)											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f mm (mm/inch)	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
20.4 (3/4)	31.750 (1 1/4)	7.838 (5/16)	0.794 (1/16)	4.782 (3/8)	3.175 (1/4)	6.350 (1/4)	1.588 (1/16)	21.828 (5/8)	27.7	14 200	16 000

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462534
Inside diameter	12.7 mm
Inside diameter	1/2" inch
Outside diameter	31.75 mm
Outside diameter	1 1/4" inch
Thickness	19.05 mm
Thickness	3/4" inch
Weight	132 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE