

## Cam follower CR22-BR-IKO - CR22-BR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr22-br-iko>

IKO

# CAM FOLLOWERS

Inch Series Cam Followers **With Cage/With Hexagon Hole**

CR22-BR

| Stud dia.<br>mm<br>(inch)   | Identification number |             |                            |                                | Mass<br>(Ref.) | g                        | D                        | C                        | d <sub>1</sub>     | G<br>UNF                 | G <sub>1</sub> |
|-----------------------------|-----------------------|-------------|----------------------------|--------------------------------|----------------|--------------------------|--------------------------|--------------------------|--------------------|--------------------------|----------------|
|                             | Shield type           | Sealed type | With covered<br>outer ring | With cylindrical<br>outer ring |                |                          |                          |                          |                    |                          |                |
| 12.700<br>( $\frac{1}{2}$ ) | CR 22                 | BR          |                            |                                | 157            | 34.925 ( $\frac{1}{2}$ ) | 19.050 ( $\frac{3}{4}$ ) | 12.700 ( $\frac{1}{2}$ ) | J <sub>1</sub> -20 | 15.875 ( $\frac{1}{2}$ ) |                |

| Boundary dimensions mm (inch) |                          |                         |                         |                         |                         |                         |                         |                          | Mounting<br>dimension<br>f<br>Min.<br>mm (inch) | Maximum<br>spinning<br>torque<br>C<br>N·m | Basic dynamic<br>load rating<br>C <sub>0</sub><br>N | Basic static<br>load rating<br>C <sub>0</sub><br>N |
|-------------------------------|--------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|--------------------------|-------------------------------------------------|-------------------------------------------|-----------------------------------------------------|----------------------------------------------------|
| B<br>max                      | B <sub>2</sub>           | B <sub>3</sub>          | C <sub>1</sub>          | G <sub>1</sub>          | G <sub>2</sub>          | H                       | r                       |                          |                                                 |                                           |                                                     |                                                    |
| 20.4 (0.80)                   | 31.750 ( $\frac{1}{2}$ ) | 7.536 ( $\frac{3}{8}$ ) | 0.794 ( $\frac{1}{8}$ ) | 4.762 ( $\frac{3}{8}$ ) | 3.175 ( $\frac{1}{4}$ ) | 6.350 ( $\frac{1}{4}$ ) | 1.588 ( $\frac{1}{8}$ ) | 21.828 ( $\frac{7}{8}$ ) | 27.7                                            | 14 200                                    | 16 000                                              |                                                    |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | IKO           |
| N° Ean13         | 3616060462565 |
| Inside diameter  | 12.7 mm       |
| Outside diameter | 34.925 mm     |
| Thickness        | 19.05 mm      |
| Weight           | 157 g         |
| Packaging        | 1             |

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE