Cam follower
CR12-UUR-IKO - CR12-UUR-IKO

https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr12-uur-iko



IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot

CR-UUR

Stud dia. mm (inch)	Identification number: Shield type, With crowned outer ring	Shield type, With cylindrical outer ring	Sealed type, With crowned outer ring	Sealed type, With cylindrical outer ring	Mass (Ref.) g	D	C	d_1	G UNF	G_1
9.525 (3/8)			CR 12 UUR		35	19.050 (3/4)	12.700 (1/2)	9.525 (3/8)	3/8 - 24	9.525 (3/8)

Boundary dimensions mm(inch) B max	B_2	B_3	C_1	g_1	g_2	r	Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N
14.2 (0.56)	22.225 (7/8)	6.350 (1/4)	0.794 (1/32)	4.762 (3/16)	2.381 (3/32)	0.794 (1/32)	13.494 (17/32)	10.8	4 420	5 110

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462855
Inside diameter	9.525 mm
Outside diameter	19.05 mm
Thickness	12.7 mm
Weight	35 g
Packaging	1

contact@123bearing.co.uk
02038 087 274
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE