


Cam follower CR14-R-IKO - CR14-R-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr14-r-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
9.525 ($\frac{3}{8}$)	CR 14 R				46	22.225 ($\frac{7}{8}$)	12.700 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	$\frac{1}{4}$ -24	9.525 ($\frac{3}{8}$)
Boundary dimensions mm(inch)					Bearing dimension f Min. mm(inch)	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	S ₁					S ₂	r
14.2938	22.225 ($\frac{7}{8}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	2.381 ($\frac{3}{32}$)	0.794 ($\frac{1}{16}$)	15.081 ($\frac{5}{8}$)	10.8	4.790	9.810

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462879
Inside diameter	9.525 mm
Outside diameter	22.225 mm
Thickness	12.7 mm
Weight	46 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE