

Cam follower CR12-VUU-IKO - CR12-VUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr12-vuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inchi)	Identification number				Mass (Ref.)	g	D	C	d ₁	G UNF	G ₁						
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With shielded outer ring	Sealed type With cylindrical outer ring													
9.525 ($\frac{3}{8}$)				CR 12 VUU	36	19.050	$\frac{7}{8}$	12.700	$\frac{7}{8}$	9.525	$\frac{7}{8}$ -24	9.525	$\frac{7}{8}$				
Boundary dimensions mm(inchi)						Mounting dimension f Min. mm(inchi)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N								
B max	B ₂	B ₃	C ₁	g ₁	g ₂					r							
14.2056	22.225	$\frac{7}{8}$	8.350	$\frac{7}{8}$	0.794	$\frac{1}{8}$	4.782	$\frac{1}{8}$	2.381	$\frac{1}{8}$	0.794	$\frac{1}{8}$	13.484	$\frac{1}{8}$	10.8	8 710	12 300

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463425
Inside diameter	9.525 mm
Outside diameter	19.05 mm
Thickness	12.7 mm
Weight	36 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE