


## Cam follower CR12-VBUUR-IKO - CR12-VBUUR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr12-vbuur-iko>

I<sup>K</sup>O

### CAM FOLLOWERS

Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR12-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Spigot type With groove outer ring	Spigot type With cylindrical outer ring							
9.525 ( $\frac{3}{8}$ )			CR 12	VBUUR	36	19.050 ( $\frac{3}{4}$ )	12.700 ( $\frac{1}{2}$ )	9.525 ( $\frac{3}{8}$ )	$\frac{1}{4}$ -24	9.525 ( $\frac{3}{8}$ )	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
14.2 0.56	22.225 ( $\frac{7}{8}$ )	6.350 ( $\frac{1}{4}$ )	0.794 ( $\frac{1}{32}$ )	4.762 ( $\frac{3}{16}$ )	2.381 ( $\frac{1}{8}$ )	4.762 ( $\frac{3}{16}$ )	0.794 ( $\frac{1}{32}$ )	13.484 ( $\frac{1}{2}$ )	10.8	8 710	12 300

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463456
Inside diameter	9.525 mm
Outside diameter	19.05 mm
Thickness	12.7 mm
Weight	36 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE