

Cam follower CR24-VUU-IKO - CR24-VUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr24-vuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inchi)	Identification number				Mass (Ref.)					
	Shield type		Sealed type		ϕ	D	C	d_1	G	G_1
15.875 ($\frac{5}{8}$)	With covered outer ring	With cylindrical outer ring	With shielded outer ring	With cylindrical outer ring						
				CR 24 VUU	230	38.100 ($\frac{1}{2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	$\frac{1}{2}$ -18	19.050 ($\frac{3}{4}$)

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque C N·m	Basic dynamic load rating C_0 N	Basic static load rating C_0 N
B max	B_2	B_3	C_1	g_1	g_2	r				
22.8 (0.90)	38.100 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{3}{16}$)	3.969 ($\frac{5}{32}$)	1.588 ($\frac{1}{16}$)	26.166 ($\frac{1}{2}$)	55.7	28 200	40 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463890
Inside diameter	15.875 mm
Outside diameter	38.1 mm
Thickness	22.225 mm
Weight	230 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE