

Cam follower CR26-V-IKO - CR26-V-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr26-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) | | | | | |
|-----------------------------|----------------------------|--------------------------------|-----------------------------|--------------------------------|----------------|--------------------------|--------------------------|--------------------------|-------------------|--------------------------|
| | Shield type | | Sealed type | | ϕ | D | C | d_1 | G | G_1 |
| | With covered outer ring | With cylindrical outer ring | With shielded outer ring | With cylindrical outer ring | | | | | UNF | |
| 15.875 ($\frac{5}{8}$) | | CR 26 V | | | 265 | 41.275 ($\frac{1}{2}$) | 22.225 ($\frac{7}{8}$) | 15.875 ($\frac{5}{8}$) | $\frac{1}{2}$ -18 | 18.050 ($\frac{7}{8}$) |

| Boundary dimensions mm(inch) | | | | | | | Mounting dimension r Min. mm(inch) | Maximum tightening torque C N·m | Basic dynamic load rating C_0 N | Basic static load rating C_0 N |
|------------------------------|--------------|-------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--|---|--|---|
| B_{max} | B_2 | B_3 | C_1 | g_1 | g_2 | r | | | | |
| 23.8 (0.94) | 38.100 (1.5) | 9.525 ($\frac{3}{8}$) | 0.794 ($\frac{1}{16}$) | 4.762 ($\frac{3}{16}$) | 3.969 ($\frac{5}{16}$) | 1.588 ($\frac{1}{16}$) | 26.166 (1.03) | 55.7 | 28 200 | 40 100 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060463951 |
| Inside diameter | 15.875 mm |
| Inside diameter | 5/8" inch |
| Outside diameter | 41.275 mm |
| Outside diameter | 1 5/8" inch |
| Thickness | 22.225 mm |
| Thickness | 7/8" inch |
| Weight | 265 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE