

## Cam follower CR26-VUU-IKO - CR26-VUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr26-vuu-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)		g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Sealed type With shield outer ring	Sealed type With cylindrical outer ring	g	kg						
15.875 (5/8)				CR 26 VUU	265	41.275 (1 5/8)	22.225 (7/8)	15.875 (5/8)		1/2-18	18.050 (7/8)	

  

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	r				
23.8 (0.94)	38.100 (1 1/2)	9.525 (3/8)	0.794 (1/16)	4.762 (3/8)	3.969 (1/4)	1.588 (1/8)	26.166 (1 1/8)	55.7	28 200	40 100

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463975
Inside diameter	15.875 mm
Inside diameter	5/8" inch
Outside diameter	41.275 mm
Outside diameter	1 5/8" inch
Thickness	22.225 mm
Thickness	7/8" inch
Weight	265 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE