


Cam follower CR28-VB-IKO - CR28-VB-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr28-vb-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers **With Cage/With Screwdriver Slot**



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
19.050 ($\frac{3}{4}$)		CR 28 VB			372	44.450 ($1\frac{7}{16}$)	25.400 (1)	19.050 ($\frac{3}{4}$)	$\frac{1}{4}$ -16	22.225 ($\frac{7}{8}$)	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum spinning torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁	g ₂					H	r
25.8106	44.450 ($1\frac{7}{16}$)	11.112 ($\frac{7}{16}$)	0.794 ($\frac{1}{16}$)	4.792 ($\frac{3}{16}$)	3.989 ($\frac{5}{32}$)	7.938 ($\frac{5}{16}$)	1.588 ($\frac{1}{16}$)	32.543 ($1\frac{1}{8}$)	100	35 300	55 600

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464071
Inside diameter	19.05 mm
Outside diameter	44.45 mm
Thickness	25.4 mm
Weight	372 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE