

## Cam follower CR30-V-IKO - CR30-V-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr30-v-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type With covered outer ring		Shield type With cylindrical outer ring		$\phi$	$D$	$C$	$d_1$	$G$ UNF	$G_1$
19.050 ( $\frac{3}{4}$ )	CR 30 V				418	47.625 ( $1\frac{7}{8}$ )	25.400 (1)	19.050 ( $\frac{7}{8}$ )	$\frac{1}{8}$ -16	22.225 ( $\frac{7}{8}$ )

  

Boundary dimensions mm(inch)							Mounting dimension $f$ Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N
$B$ max	$B_2$	$B_3$	$C_1$	$g_1$	$g_2$	$r$				
25.8 (1.00)	44.650 ( $1\frac{3}{4}$ )	11.112 ( $\frac{1}{2}$ )	0.794 ( $\frac{1}{4}$ )	4.782 ( $\frac{1}{4}$ )	3.969 ( $\frac{1}{4}$ )	1.588 ( $\frac{1}{4}$ )	32.543 ( $1\frac{1}{4}$ )	100	35 300	55 800

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464101
Inside diameter	19.05 mm
Outside diameter	47.625 mm
Thickness	25.4 mm
Weight	418 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE