

Cam follower CR30-VUU-IKO - CR30-VUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/cr30-vuu-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type		Sealed type		ϕ	D	C	d_1	G	G_1
19.050 ($\frac{3}{4}$)	With covered outer ring	With cylindrical outer ring	With shielded outer ring	With cylindrical outer ring						
				CR 30 VUU	418	47.625 ($\frac{1 7}{8}$)	25.400 (1)	19.050 ($\frac{3}{4}$)	$\frac{1}{4}$ -16	22.225 ($\frac{7}{8}$)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N		
B_{max}	B_2	B_3	C_1	g_1					g_2	r
25.8100	44.450 ($\frac{1 3}{8}$)	11.112 ($\frac{1}{2}$)	0.794 ($\frac{1}{16}$)	4.762 ($\frac{1}{4}$)	3.969 ($\frac{3}{16}$)	1.588 ($\frac{1}{16}$)	32.543 ($\frac{1 1}{8}$)	100	35 300	55 800

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464125
Inside diameter	19.05 mm
Outside diameter	47.625 mm
Thickness	25.4 mm
Weight	418 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE