


## Cam follower CRH24-VUU-IKO - CRH24-VUU-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/crh24-vuu-iko>

IKO

### CAM FOLLOWERS

Inch Series Heavy Duty Cam Followers Full Complement Type/With Screwdriver Slot



CRH-VUU

Stud dia. mm (inch)	Identification number		Mass (Ref.) g	D	C	d <sub>1</sub>	G LINE	G <sub>1</sub>	B max
	Shield type	Sealed type							
22.225 ( <sup>7</sup> / <sub>16</sub> )	CRH 24	VUU	296	38.100 ( <sup>1</sup> / <sub>2</sub> )	22.225 ( <sup>7</sup> / <sub>16</sub> )	22.225 ( <sup>7</sup> / <sub>16</sub> )	<sup>7</sup> / <sub>16</sub> -14	19.050 ( <sup>3</sup> / <sub>4</sub> )	24.319 (96)
Boundary dimensions mm(inch)				Mounting dimension f mm(inch)	Maximum operating temp C	Basic dynamic load rating C <sub>10</sub>	Basic static load rating C <sub>0</sub>		
B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	S <sub>1</sub>					S <sub>2</sub>	r
38.100 ( <sup>1</sup> / <sub>2</sub> )	8.525 ( <sup>5</sup> / <sub>16</sub> )	1.588 ( <sup>5</sup> / <sub>16</sub> )	4.782 ( <sup>3</sup> / <sub>16</sub> )	2.381 ( <sup>3</sup> / <sub>16</sub> )	1.588 ( <sup>5</sup> / <sub>16</sub> )	26.988 ( <sup>1</sup> / <sub>2</sub> )	182	28 200	40 100

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060464613
Inside diameter	22.225 mm
Outside diameter	38.1 mm
Thickness	22.225 mm
Weight	296 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE