


Cam follower CRH36-VBUUR-IKO - CRH36-VBUUR-IKO

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/cam-follower/crh36-vbuur-iko>

IKO

CAM FOLLOWERS

Inch Series Heavy Duty Cam Followers **Full Complement Type/With Hexagon Hole**



CRH36-VBUUR

Stud dia. mm (inch)	Identification number		Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	B max
	Shield type	Sealed type							
28.575 (1.125)	CRH 36	VBUUR	858	57.150 (2.25)	31.750 (1.25)	28.575 (1.125)	1/2-12	25.400 (1)	34.2 (1.35)

Boundary dimensions mm(inch)								Mounting dimension F Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
B ₂	B ₃	C ₁	S ₁	S ₂	H	R					
50.800 (2)	12.700 (1/2)	1.988 (3/8)	4.762 (3/4)	3.175 (1/4)	11.112 (3/4)	600.36	37.306 (1.5)	358	45 700	80 800	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952463841
Inside diameter	28.575 mm
Outside diameter	57.15 mm
Thickness	31.75 mm
Weight	858 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE