


## Roller bearing NN3052K-JTEKT - NN3052K-KOYO

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nn3052k-koyo>

### Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.	
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>C</i>	<i>C<sub>02</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
260	400	104	4	—	364	1 030	1 300	1 500		<b>NN3052K</b>

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d<sub>a</sub></i>		<i>D<sub>a</sub></i>		<i>r<sub>a</sub></i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		276	—	—	384	367	3	47.4	46.0

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952473932
Inside diameter	260 mm
Outside diameter	400 mm
Thickness	104 mm
Weight	46000 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE