

Roller bearing NQ40-20-JTEKT - NQ40-20-KOYO

<https://www.123bearing.co.uk/bearing-housing/roller-bearing/roller/nq40-20-koyo>

Machined ring needle roller bearings ————— **Koyo**
F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.		Without inner ring	
40	35	50	20	—	0.3	27.2	48.8	12 000	NQ40/20
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				d ₁ min.	D ₁ max.	r _a max.	Without inner ring	With inner ring	
				37	48	0.3	0.085	0.129	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483030
Inside diameter	40 mm
Outside diameter	50 mm
Thickness	20 mm
Weight	85 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE