

Axial needle roller AZ456514-IKO - AZ456514-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/axial-needle/az456514-iko>

IKO
THRUST BEARINGS

Thrust Roller Bearings

Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
45	AZ 456514	169	AZK 45656	62	WS 4565	GS 4565	53.5	

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C0	Allowable rotational speed ⁽²⁾
d	D	T	d _c	D _c	D _w	B	F _{max} ⁽¹⁾	C ₁	C ₀	d ₄ Min.	D ₄ Max.	N	N	rpm
45	65	14	45.05	64.5	6	4	0.6	49	62	62	49	40 800	133 000	5 500

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension F
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060465962
Inside diameter	45 mm
Outside diameter	65 mm
Thickness	14 mm
Weight	169 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE