


Axial needle roller AZK24031524-IKO - AZK24031524-IKO

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/axial-needle/azk24031524-iko>

IKO
THRUST BEARINGS

Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
240	AZ 24031554	13 200	AZK 24031524	5 520	WS 240315	GS 240315	3 840

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾
d	D	T	d _c	D _c	D _w	B	r _s ⁽¹⁾	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
240	315	54	240.15	314	24	15	2	256	304	302	257	695 000	3 250 000	1 100

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952487953
Inside diameter	240 mm
Outside diameter	315 mm
Thickness	24 mm
Weight	5520 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE