


Thrust washer GS130185-IKO - GS130185-IKO

<https://www.123bearing.co.uk/accessories/washer/thrust-washer/gs130185-iko>

IKO

THRUST BEARINGS

Thrust Roller Bearings



| Shaft dia. mm | Identification number | | | | | | | |
|------------------|-----------------------|---------------|-----------------------|---------------|------------------|------------------|---------------|-------|
| | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g | |
| 130 | AZ 13018542 | 4 300 | AZK 13018518 | 1 780 | WS 130185 | GS 130185 | | 1 270 |

| Boundary dimensions mm | | | | | | | | | | Standard mounting dimensions mm | | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ |
|---------------------------|-----|----|----------------|----------------|----------------|----|--------------------|----------------|----------------|------------------------------------|------------------------|-----------------------------------|---|---|
| d | D | T | d _c | D _c | D _w | B | r _s (1) | C ₁ | C ₂ | d _s Min. | D _s Max. | N | N | rpm |
| 130 | 185 | 42 | 130.1 | 184.5 | 18 | 12 | 1.5 | 142 | 178 | 177 | 143 | 333 000 | 1 290 000 | 1 900 |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060467072 |
| Inside diameter | 130 mm |
| Outside diameter | 185 mm |
| Thickness | 12 mm |
| Material | STEEL |
| Weight | 1270 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE