


Thrust washer GS180310-IKO - GS180310-IKO

<https://www.123bearing.co.uk/accessories/washer/thrust-washer/gs180310-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings



| Shaft dia. mm | Identification number | | | | | | |
|---------------|-----------------------|---------------|-----------------------|---------------|------------|------------|---------------|
| | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g |
| 180 | AZ 18031039 | 14 600 | AZK 18031015 | 5 200 | WS 180310 | GS 180310 | 4 700 |

| Boundary dimensions mm | | | | | | | | | | Standard mounting dimensions mm | | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ^(*) |
|------------------------|-----|----|----------------|----------------|----------------|----|--------------------|----------------|----------------|---------------------------------|---------------------|-----------------------------|---|---|
| d | D | T | d _c | D _c | D _w | B | r _s (1) | C ₁ | C ₂ | d _s Min. | D _s Max. | N | N | rpm |
| 180 | 310 | 39 | 180.1 | 308 | 15 | 12 | 3 | 204 | 294 | 293 | 205 | 619 000 | 3 710 000 | 1 200 |

Notes: (*) Minimum allowable value of chamfer dimension r
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3616060467324 |
| Inside diameter | 180 mm |
| Outside diameter | 310 mm |
| Thickness | 12 mm |
| Material | STEEL |
| Weight | 4700 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE