

SI Rod end DSI5-T-K-DURBAL - SI5-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/si5-t-k-durbal>

DSI5-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
DSI 5 T/K			d	G	B	C ₁	d ₂	d ₃	d ₄
			5	M 5	8	6,00	18	8,5	11

type	measurement [mm]			d ₁ PT	load rating C ₀ [N]	weight [kg]
	l ₁ min	W	h			
DSI / DSIL 5 T/K	10	9	27	13	6,0	0,016

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489056
Inside diameter	5 mm
Outside diameter	18 mm
Thickness	8 mm
Type	SI
Weight	16 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE