

## SI Rod end DSIL5-T-K-DURBAL - SIL5-T-K-DURBAL

https://www.123bearing.co.uk/bearing-housing/rod-end/si/sil5-t-k-durbal


### DSIL5-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number	right hand thread	left hand thread	measurement (mm)						
DSIL 5 T/K			d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
			5	M 5	8	6,00	18	8,5	11

type	measurement (mm)			h	d <sub>1</sub> PT	load rating C <sub>0</sub> (N)	weight (kg)
	l <sub>1</sub> min	W					
DSI / DSIL 5 T/K	10	9	27	13	6,0	0,016	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489070
Inside diameter	5 mm
Outside diameter	18 mm
Thickness	8 mm
Type	SI
Weight	16 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE