

SI Rod end SI12-T-K-DURBAL - SI12-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/si12-t-k-durbal>

SI12-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 12 TIK		12	M 12	16	12,00	32	17,5	22

type	measurement [mm]			load rating C ₁₀ [N]	weight [g]
	l ₁ min	W	h		
SI / SI12 TIK	22	19	50	24,0	0,100

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489285
Inside diameter	12 mm
Outside diameter	32 mm
Thickness	16 mm
Type	SI
Weight	100 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE