

## SI Rod end SI20-T-K-DURBAL - SI20-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/si20-t-k-durbal>

### SI20-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and  
spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race  
lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number	right hand thread	left hand thread	measurement [mm]						
			d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SI 20 TIK			20	M 20 x 1,5	25	18,00	50	27,5	34

type	measurement [mm]			d <sub>1</sub> PT	load rating C <sub>0</sub> [N]	weight [kg]
	l <sub>1</sub> min	W	h			
SI / SIH 20 TIK	33	30	77	14	57,0	0,420

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489537
Inside diameter	20 mm
Outside diameter	50 mm
Thickness	25 mm
Type	SI
Weight	420 g
Thread	Right-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE