

SI Rod end SIL40-T-K-DURBAL - SIL40-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/sil40-t-k-durbal>


SIL40-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated

sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
	SIL 40 T/K	40	M 42 x 2	49	33,00	91	53,0	65

type	measurement [mm]			load rating C ₀ [kN]	weight [kg]
	l ₃ min	W	h		
SI / SIL 40 T/K	60	55	142	17	2,400

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952489810
Inside diameter	40 mm
Outside diameter	91 mm
Thickness	49 mm
Type	SI
Weight	2400 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE