

SA Rod end SAL8-T-K-DURBAL - SAL8-T-K-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sal8-t-k-durbal>


SAL8-T-K



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 8 T/K		8	M 8	12	9,00	24

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 8 T/K	25		42	14	12,9	0,038

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952490007
Inside diameter	8 mm
Outside diameter	24 mm
Thickness	12 mm
Type	SA
Weight	38 g
Thread	Left-hand thread
Lubrication	without
Packaging	-
Standard	No standard

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE