

**SA Rod end**  
**SAL16-T-K-DURBAL - SAL16-T-K-DURBAL**  
<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sal16-t-k-durbal>

**SAL16-T-K**



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**male thread:** maintenance free, according to DIN ISO 12240-4, series K

**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

order number	measurement [mm]		C <sub>1</sub>	d <sub>2</sub>
	d	G		
SAL 16 T/K	16	M 16	21	15,00

  

type	measurement [mm]		h	α [°]	Tragzahlen C <sub>10</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>				
SA / SAL 16 T/K	37	21	66	15	39,0	0,210

**PRODUCT FEATURES**

Brand	DURBAL
N° Ean13	3663952490168
Inside diameter	16 mm
Outside diameter	42 mm
Thickness	21 mm
Type	SA
Weight	210 g
Thread	Left-hand thread
Lubrication	without
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)  
02038 087 274  
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE